

LIGHTNING™

Multi-Purpose Night Vision Monocular



Lightning™
c/w Optional
Headmount



Lightning™
c/w Optional
100mm f1.5



Lightning™ with AimPoint/
QR weapon mount
on H&K G36



Lightning™
c/w Optional 3x
Lens Converter



Lightning™
c/w Optional EOTech
weapon mount
(Aimpoint also available)



Lightning™
c/w Optional
165mm f2.0



- Gen 2+/SuperGen/HyperGen IIT • Compact & Lightweight
- Long eye relief - 30mm • 26mm f1.1/26mm f1.2 lens • 1.0x magnification • FOV 40°
- Automatic Brightness Control • Built-in Tripod Socket • Weather resistant
- Supplied complete with SLR/Video camera adaptor
- *Optional 7013 100mm f1.5 (4.0x mag) & 7015 165mm f2.0 (6.3x mag) lenses*
- *Optional 7029 3.0x Lens Converter*
- *Optional 50/75/150/200mW high power IR illuminators*
- *Optional 7040 Headmount • Optional 7051 Helmet Mount • Optional Weapon Mount*

AVAILABLE INTENSIFIER TUBE OPTIONS

Russian Gen 2+ • Photonis-DEP MilSpec Gen 2+ • Photonis-DEP MilSpec SHD-3/SuperGen
Photonis-DEP XD-4/HyperGen • Photonis-DEP XR-5/Auto-Gating HyperGen

Dimensions:	115 x 67 x 48mm	Eyepiece:	+2, -5 dioptres
Weight:	0.38kg	IR Illuminator:	Built-in
Objective Lens:	1 x 26mm f1.1 <i>Optional - 100mm f1.5/165mm f2.0</i>	Battery :	2 x LR6/MN1500/AA 1.5V Alkaline
Magnification:	1.0x (26mm)/3.9x (100mm)/6.3x (165mm)	Temp. range:	-40 °C - +50 °C
Field of view:	40° (26mm)/10° (100mm)/6.5° (165mm)	Humidity:	80% RH @ +20 °C
Focusing:	0.25m (26mm) - ∞	Guarantee:	1 Year Exchange